## **Technical data sheet**

Cover, 90° bend A4

**Item number: 6036998** 



Cover for 90° bend fitting for lockable and screw-on cable trays in indoor and out-door areas, to protect cables against damage and soiling. Fastening with pre-mounted sash lock and through attachment of the section cover. Suitable for all side heights.

The cover can be used with fittings of all side heights.



# CER

Α4

Stainless steel

2E

Bright, treated

#### Master data

| Item number                            | 6036998                   |
|--|---------------------------|
| Туре                                   | RBD 90 600 A4             |
| Description 1                          | Cover                     |
| Description 2                          | for 90° bend              |
| Manufacturer                           | OBO                       |
| Dimension                              | B600mm                    |
| Colour                                 | stainless steel           |
| Material                               | Stainless steel           |
| Surface                                | Bright, treated           |
| Surface standard                       |                           |
| Smallest sales unit                    | 1                         |
| Unit of quantity                       | Piece                     |
| Weight                                 | 280 kg                    |
| Weight unit                            | kg/100 pc.                |
| CO2 Footprint (GWP) Cradle-to-<br>Gate | 37,8125 kg CO2e / 1 Piece |
|  | •                         |


# **Technical data sheet**

## Cover, 90° bend A4

**Item number: 6036998** 



### Dimensions



| Length          | 658 mm |
|-----------------|--------|
| Width           | 600 mm |
| Plate thickness | 1 mm   |
| Dimension B     | 600 mm |

### Technical data

| Bend (angle)                  | 90°        |
|-------------------------------|------------|
| Number of turn buckles        | 1 St.      |
| Fastening type                | Sash lock  |
| Maintain electrical functions | no         |
| Suitable for mesh cable tray  | no         |
| Suitable for cable ladder     | no         |
| Suitable for cable tray       | yes        |
| Change of direction           | Horizontal |
| Rustproof steel, pickled      | no         |
| Hinged                        | no         |
| Permitted temperature range,  | 120 °C     |
| max.                          |            |
| Permitted temperature range,  | -20 °C     |