## **Technical data sheet**

### Junction box T250, closed, elevated cover

Item number: 2007736





Closed junction box for the connection of cables in indoor and protected outdoor areas. Rectangular design without entries. Suitable for wall and ceiling mounting, on mounting panels and threads in the floor. With the option of fastening inside and to mount via the corner domes. High cover with quick lock, sealable. Made from halogen-free, UV-resistant materials.

With hat profile rail.

Junction box according to DIN EN 60670. Flame-resistant to DIN EN 60695/2/11, test temperature  $650^{\circ}$ C. Impact resistance IK05 according to DIN EN 50102. Clear internal dimensions: 225x173x102 mm















Polypropylene / polycarbonate

#### Master data


2007736
Junction box, closed
with raised cover
OBO
240x190x115
Light grey; RAL 7035
Polypropylene / polycarbonate
1
Piece
50.57 kg
kg/100 pc.
2,2822 kg COe / 1 Piece

# **Technical data sheet**

## Junction box T250, closed, elevated cover



**Item number: 2007736** 



#### Technical data

- <u>-</u>	
Expandable	yes
Type of insertion	None
Type of entry	Cable
Type of housing penetration	Without
Measured insulation voltage Vi	500 V
Equipment	Without
Cover	Not transparent
Cover fastening	Screwed
Entry from rear	yes
Entries	None
Explosion-tested version	no
Flame-resistant	acc. to VDE 0471/DIN 695 Part 2-1, test temperature 650°C
Shape	Rectangular
Maintain electrical functions	Without
For Ex zone	Without
For Ex zone gas	Without
For Ex zone dust	Without
Fibre-glass reinforced	yes
Halogen-free	yes
Clear internal dimensions	225x173x102 mm
With screening	no
with lid	yes
Mounting type	Wall/ceiling mounting
Nominal voltage	500 V
Sealable	yes
Protection rating	IP66
Protection rating IK code	IK05.
Permitted temperature range, max.	60 °C
Permitted temperature range, min.	-5 °C

240 mm 190 mm

112 mm

# **Technical data sheet**

Junction box T250, closed, elevated cover

**Item number: 2007736** 



Technical data		
	Weatherproof	no